

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance yarns, Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

BARSTOW SPECIFICATIONS

CONTENT

BACKING

FINISH

WEIGHT

WIDTH

ROLL SIZE

· 90% polyester

acrylic latex

CryptonWall® 'Green' 16 oz.

54" 50 yards

· 10% olefin

Soil & Stain Repellant

15% RECYCLED CONTENT

· 5% post-consumer · 10% post-industrial

FLAMMABILITY

Passes: UBC 8-2 Corner Burn Class A / ASTM E-84

FS: 20 / SD: 50 Passes: Cal 117 Passes: Vertical Burn **ABRASION RESISTANCE**

(ASTM D-4157-02) 100,000 double rubs **COLOR FASTNESS TO LIGHT**

(AATCC-16A) Class 5.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- · pvc
- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- requires less energy to produce

Greenguard Gold Certified

- Number 23850-410
- · formerly Children & Schools Gold Certified
- · meets Calif 1350 High Performance Schools

