

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance yarns, Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

TENACITY SPECIFICATIONS

CONTENTBACKINGFINISHWEIGHTWIDTHROLL SIZE80% polyesteracrylic latexCryptonWall® 'Green'18 oz.54"50 yards

· 80% polyester acrylic latex Crypton · 20% olefin Soil 8

Soil & Stain Repellant

RECYCLED

· 20% post-industrial (olefin)

FLAMMABILITY

Passes: UBC 8-2 Corner Burn Class A / ASTM E-84 FS: 20 / SD: 50 Passes: Cal 117

Passes: Cal 117
Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02) 100,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A) Class 5.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- · pvc
- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

Greenguard Gold Certified

- Number 23850-410
- · formerly Children & Schools Gold Certified
- meets Calif 1350 High Performance Schools



[©] Hytex Industries, Inc. 2016 All rights reserved.