BOUCLE

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

Inspired by a woven classic, this fashionable fiber mix dresses up any vertical surface with its

combination of refined warp yarns offset by subtly variegated boucle filling yarns.

SPECIFICATIONS

WIDTH:	54"	BACKING:	Acrylic
TOTAL WEIGHT:	15 oz. per linear yard	INSTALLATION:	Non-Reversible / Random Match
FINISH:	Stain Repellent	CONTENT:	100% Polyester

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A
	Tested in Accordance with CAN/ULC-S102
	Tested in Accordance with (EN13501): B-s1,d0 rating
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 4 (40 hours)
ABRASION RESISTANCE:	(ASTM D4157) Exceeds 30,000 Wyzenbeek Double Rubs

QUALITY STANDARDS

ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde,
	No ODS's, No Phthalates, No VOC's
CLEANING CODE:	WS & BC – Water/Solvent & Bleach Cleanable

INSTALLATION

Color & texture may vary slightly due to the nature of the fiber & structure. Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations
- HOSPITALITY
- Ball Rooms
- Conference Rooms
- Meeting Rooms
- DESIGNERS
- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center





The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.