

# CADENCE

## HIGH PERFORMANCE WOVENS

### Wallcoverings • Panels • Exhibits • Partitions

High performance yarns blend with natural linen filaments in a masterful mix of technology and nature for enhanced durability with soft classic sophistication.

#### SPECIFICATIONS

WIDTH:	54"	INSTALLATION:	Non-Reversible / Random Match
TOTAL WEIGHT:	11 oz. per linear yard	CONTENT:	35% Polyethylene, 35% Linen, 30% Polyester
BACKING:	Non-Woven		
FINISH:	None		

#### PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 5 (40 hours)
COLORFASTNESS TO CROCKING:	(AATCC Method 8): Class 4 (Wet), Class 5 (Dry)
ABRASION RESISTANCE:	(ASTM D4157) 87,500 Wyzenbeek Double Rubs

#### QUALITY STANDARDS

ENVIRONMENTAL:	PVC-Free
CLEANING CODE:	WS & BC – Water/Solvent & Bleach Cleanable

#### INSTALLATION

Color & texture may vary slightly due to the reflective quality of the yarn.  
Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation.  
For best results, it is recommended that a qualified textile wallcovering installer be employed.  
Customs available upon request.

#### WARRANTY

5-year limited warranty against manufacturing defects.

#### USAGE AREAS

##### HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

##### HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

##### DESIGNERS

- Commercial Interiors Market

##### ENTERTAINMENT

- Theatres
- Recreational Centers

##### CORPORATE

- Executive Conference Rooms
- General Offices

##### INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center