CRESPELLA

ACOUSTIC WALLCOVERINGS

Wallcoverings • Panels • Exhibits • Partitions

This luxurious, deeply sculpted, folded, embossed fabric is created from sound-

softening sustainable yarns made from 100% recycled polyester fiber.

SPECIFICATIONS Design Copyright © York Contract

WIDTH:	54"		BACKING:	Fused Poly
TOTAL WEIGHT:	24 oz. per linear y		INSTALLATION:	Non-Reversible / Random Match
THICKNESS:	Approximately 2.5		CONTENT:	Recycled Polyester
PERFORMANCE		LENGTH:	33 yards	
FLAMMABILITY:		Passes ASTM E-84 Cla: Tested in Accordance wi Tested in Accordance wi	th CAN/ULC-S102	ig (after FR treatment by York)
COLORFASTNESS TO LIGHT:		(AATCC Method 16): Class 5 (40 hours)		
COLORFASTNESS TO CROCKING:		(AATCC Method 8): Class 4.5 (Wet), Class 4.5 (Dry)		
ABRASION RESISTANCE:		Full Commercial Serviceability		
ACOUSTICAL NRC (ASTM C-423):		0.20 over gypsum board (*Base NRC value is 0.20 before etching/sculpting*)		

QUALITY STANDARDS

Created with No PVC, No Heavy Metals or Formaldehyde,		
ment of Health Services		

INSTALLATION

Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

HEALTH CARE HOSPITALITY • Retirement Facilities • Conference Rooms • Nursing Homes • Meeting Rooms • Hospitals • Nursing Stations DESIGNERS • Commercial Interiors Market	ENTERTAINMENT • Theatres • Recreational Centers CORPORATE • Executive Conference Rooms • General Offices	INSTITUTIONAL • Schools (Auditorium) • Government & Mass Trans. Buildings • Day Care Center
--	---	--



The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.