

HURON

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

Inspired by the tranquil impression of sunlight reflecting off still water, fine points of light are dispersed evenly throughout the design by high sheen filaments to imply subtle currents.

SPECIFICATIONS

WIDTH:	54"	INSTALLATION:	Non-Reversible / Random Match
TOTAL WEIGHT:	13 oz. per linear yard	CONTENT:	64% Polyester,
FINISH:	Stain Repellent		8% Post-Industrial Recycled Polyester,
BACKING:	Acrylic		4% Post-Consumer Recycled Polyester,
			24% Olefin

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102 Tested in Accordance with (EN13501): B-s1,d0 rating
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 5 (40 hours)
ABRASION RESISTANCE:	(ASTM D4157) Exceeds 100,000 Wyzenbeek Double Rubs (Cotton Duck)

QUALITY STANDARDS

ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde, No ODS's, No Phthalates, No VOC's
SUSTAINABLE MATERIALS:	Produced Using Recycled Content
CLEANING CODE:	WS & BC - Water/Solvent & Bleach Cleanable
LEED CONTRIBUTION:	Can Contribute Towards LEED Points

INSTALLATION

Color & texture may vary slightly due to the nature of the fiber & structure.
Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation.
For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center