

# HIGH PERFORMANCE FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

Treated with Stainguard. Stainguard's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment for your customers.

---

## SATINE SPECIFICATIONS

### CONTENT

· 100% polyester

### BACKING

acrylic latex

### FINISH

Stainguard

### WEIGHT

13 oz.

### WIDTH

54"

### ROLL SIZE

50 yards

### FLAMMABILITY

Passes: UBC 8-2  
Class A / ASTM E-84  
FS: 25 / SD: 25  
Passes: Cal 117  
Passes: Vertical Burn

### ABRASION RESISTANCE

(ASTM D-4157-02)  
30,000 double rubs

### COLOR FASTNESS TO LIGHT

(AATCC-16A)  
exceeds Class 4.0 / 40 hrs.

### ENVIRONMENTAL

#### does not contain:

- pvc
- chlorene
- plasticizers
- heavy metals
- formaldehyde
- ozone depleting substances
- volatile organic chemicals (voc's)

© Hytex Industries, Inc. 2017 All rights reserved.

Copyright © 2017 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™ and all products denoted with ® or ™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.