

# HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

Subtle highlights of sheen and a rugged textural weave provide an elegant anchoring complement to a wide range of design aesthetics that is both beautiful and durable.

### **SPECIFICATIONS**

WIDTH: 54" BACKING: Acrylic Latex

TOTAL WEIGHT: 13 oz. per linear yard INSTALLATION: Non-Reversible / Random Match

FINISH: Stain Repellent CONTENT: 100% Polyester

### PERFORMANCE

FLAMMABILITY: Passes ASTM E-84 Class A

Tested in Accordance with CAN/ULC-S102

Tested in Accordance with (EN13501): B-s1,d0 rating

COLORFASTNESS TO LIGHT: (AATCC Method 16): Class 4 (40 hours)

ABRASION RESISTANCE: (ASTM D4157) Exceeds 30,000 Wyzenbeek Double Rubs

## **QUALITY STANDARDS**

ENVIRONMENTAL: Created with No PVC, No Heavy Metals or Formaldehyde,

No ODS's, No Phthalates, No VOC's

CLEANING CODE: WS & BC - Water/Solvent & Bleach Cleanable

### INSTALLATION

Customs available upon request. Color & Texture May Vary Slightly Due to the Reflective Quality of the Yarn. Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.

#### WARRANTY

5-year limited warranty against manufacturing defects.

# **USAGE AREAS**

### HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

#### HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

#### **DESIGNERS**

• Commercial Interiors Market

### ENTERTAINMENT

- Theatres
- Recreational Centers

### CORPORATE

- Executive Conference Rooms
- General Offices

# INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center



